


FOCUS ON Linear

Ceiling systems

PRACTICAL AND ELEGANT
IN LINE WITH YOUR STYLE





Linear Ceiling systems


Endless possibilities to create structure and chaos

Project : Food Market, Romania
Product : 84R Curved Metal Ceiling system
Architect: nn

Structure and chaos

With our Linear Ceiling systems you can create either structure or chaos by using just the most well-known and honest ceiling system ever made. From 30 up to 300 mm and another 8 widths in between there are endless possibilities to design your own style.

Our Linear Ceiling systems highlight versatility, allowing a variety of visual effects, including radial and diagonal patterns and curves. You can choose from standard available colours, including 5 wood patterns or make up your own custom colours and mix and match different widths and heights to create the perfect look.





The benefits of a Linear Ceiling system

Visual and acoustic comfort in one versatile Ceiling System.

- Endless design options
- Can be customised to your needs
- Open space for integrated technology
- Easy installation with standard carriers
- Compliant with all safety regulations

Design options

Our Linear Ceiling systems are available in a wide range of materials, colours and designs, including wood décor and steel. Straight, meandering or undulating shapes can be produced to create character and atmosphere in a wide range of interior spaces.

The Hunter Douglas Linear Ceiling systems ensures a perfect linear appearance with excellent acoustic performance. Our Linear Ceilings are particularly suitable for use in areas where acoustic performance is critical such as schools, libraries, shopping malls, indoor sporting arena, public lounges and transport hubs.

CONTENT	Page
Linear closed	
• 75C - 150C - 225C	4
• 84C	6
Linear open	
• Multipanel	8
• CCA	10
• 80B / 84B	12
• 84R	14
• 70U	16
Wide Panel	
• 300C / 300L	18
Curved	
• 84R / 300C	20
• Curved Carrier	22
Hunter Douglas Architectural	23

HunterDouglas 
Architectural



Production by
Hunter Douglas
Ceiling Center



Cover : Groninger Forum, The Netherlands
Product : 30BD Linear Ceiling system

Designed to work for you

Linear Closed

75C - 150C - 225C


Create subtle patterns for a closed smooth ceiling

Hunter Douglas Closed Linear panels put less emphasis on the direction of the panels, an important aspect when a designer is looking to achieve a closed smooth ceiling. Three different widths in a uni design or combined with each other, create subtle patterns that can produce a stunning finish to any ceilings appearance.



Project : Lodz University, Lodz, Poland
Product : 75C-150C-225C Linear Ceiling system
Architect: OOA

System composition



HunterDouglas® 75C-150C-225C Linear Ceiling system

Left : Midsummer place shopping centre, Milton Keynes, United Kingdom
Product: 150C Linear Curved Carrier Ceiling system
Photo : Greig Stephenson GMW London

Dimensions & Colours

The panels with widths of 75, 150 and 225 mm can be fixed to a universal carrier, all the same or mixed. The panels are available in length from 800 to 6000 mm and are joined together using a panel splice whilst the carriers use the standard carrier connector. Adaptor panels are locked by the adaptor clip.



A wide range of finishes are available including wood décor (75C) or on request in any desired RAL colour (min. quantities apply). See our colour card and availability chart on the website for standard available colours.

Design elements

Linear panels provide interesting possibilities for directional room designing. Our ceiling systems highlight versatility, allowing a variety of visual effects, including radial and diagonal patterns.

The Linear 75C - 150C - 225C ceiling system from Hunter Douglas provide the architect and designer with an opportunity to create a closed smooth ceiling.

Below : Sir Robert Gordon university, Aberdeen, United Kingdom
Product : 150C Linear Ceiling system
Architect: Foster Partners




Above : Dodoens Hospital, Mechelen , Belgium
Product : 225C Linear Ceiling system
Architect: Luyten Lens

Key features

75C-150C-225C LINEAR CLOSED CEILING PANELS

- Panel widths: 75 mm, 150 mm and 225 mm
- Panel length: 800 mm up to 6000 mm
- Panel depth 15 mm
- Bevelled edge design
- Interior and exterior applications
- On site waste reduction with factory fabricated dimensional material
- Easy plenum access
- Compatible with industry standard lighting, HVAC, speaker, fire safety, and security services.




84C

A ceiling with stylish linear patterns

The HunterDouglas® 84C recessed joint aluminum panels can be specified to emphasize the direction of the panels. This easy to install closed ceiling system allows the architect to create stylish linear patterns with a sturdy character. The panels can also include a closed flange with slot perforation for better ventilation and combined with modern and functional lighting.



System composition



HunterDouglas® 84C Linear Ceiling system

Left : Toei Oedo Line ShinEkoda Station, Tokyo, Japan
Product : 84C Linear Metal Ceiling
Architect: Tokyo Metropolitan Government Bureau of Transportation

Dimensions & Colours

The 84C closed ceiling system consists of box shaped panels, that can be easily clipped onto a carrier system.

The 84 mm wide panels feature a 24 mm wide flange that closes-off the 16 mm joint between the panels. The system module is 100 mm. Panels are demountable for easy access to the plenum.

See our colour card and availability chart on the website for standard available colours.

Application


The 84C Closed aluminium ceiling panel is suitable for all building sectors including Corporate, Transport (airports, metro, bus and train stations), Retail, Leisure, Public space, Hospitality, Healthcare, Education and Residential.

Key features

84C LINEAR CLOSED CEILING PANELS

- Panel width 84 mm, joint 16 mm
- Panel length: 800 mm up to 6000 mm
- Panel depth 12.5 mm
- Optimum acoustic control using perforated panels with a non-woven textile
- Interior and exterior applications
- On site waste reduction with factory fabricated dimensional material
- Easy plenum access
- Compatible with industry standard lighting, HVAC, speaker, fire safety, and security services.

84C Linear panel



Below : Toei Oedo Line ShinEkoda Station, Tokyo, Japan
Product : 84C Linear Metal Ceiling
Architect: Tokyo Metropolitan Government Bureau of Transportation






Multipanel


Combine and create excitement

Mix and match the diverse B, BD and the BXD ceiling panels by combining varying widths and heights. Control acoustics with the perforated panels and create an improved interior ambience. Save installation time because all 8 different panels can be combined on one carrier system. A key feature of this system is the unlimited combinations that can be achieved by varying depths and widths. This gives architects the freedom to design a ceiling with the excitement they are aiming for.

System composition



HunterDouglas® Multipanel Ceiling system



Project : Alexander station, Rotterdam, The Netherlands
Product : Multipanel Ceiling system
Architect: OPL Architects

Left : Leaseplan Branch Office, Milano, Italy
Product : Multipanel Ceiling system
Architect: Progetto CMR

Dimensions & Colours



The BXD Ceiling panels (height 64 mm) are available in three widths: 30, 80 and 130 mm which can be used in combination with the B panels (height 15 mm), and BD panels (height 39 mm) from the Hunter Douglas Multi-Panel ceiling program. This unique pairing of ceiling solutions makes it possible to create highly functional and beautifully engineered three-dimensional designs.

The wide choice of colours available make it possible to create virtually any ceiling design you can imagine. See our colour card and availability chart on the website for standard available colours.

Design elements

The 20 mm joints can be left open or closed with a V-shaped or U-shaped joint profile.

Dimensions Multipanel panels



Key features

LINEAR OPEN MULTIPANEL CEILING

- Panel widths: 30 mm, 80 mm, 130 mm and 180 mm, joint width 20 mm
- Panel length: 800 mm up to 6000 mm
- Panel depths: 15 mm, 39 mm, 64 mm
- Curved carrier application available
- On site waste reduction with factory fabricated dimensional material
- Easy plenum access
- Compatible with industry standard lighting, HVAC, speaker, fire safety, and security services


Linear Open




CCA

Enhance comfort with Concrete Core Activation (CCA)

The excellent thermal exchange and acoustic performance of the Luxalon® Linear Open CCA Ceiling system provides 100% acoustic ceiling coverage. This acoustic ceiling creates outstanding comfort and temperature control at levels that cannot be achieved with islands or baffle systems.



System composition



Luxalon® CCA 30BD Linear Ceiling system

Left : Waterschap Brabantse Delta, Breda, The Netherlands
 Product : CCA 30BD Linear Ceiling system
 Architect: Claus en Kaan Architecten Rotterdam


Dimensions & Colours

The CCA panels come in two heights: 39 and 64 mm which are also used in the Hunter Douglas Multi-Panel ceiling program. As a special there is a 60 mm module carrier available with an open joint width of 30 mm to enhance the thermal performance of the CCA panel system.

A standard range of finishes is available, also in steel, or on request in any desired RAL or custom colour. See our colour card and availability chart on the website for standard available colours.

Design elements

This unique pairing of ceiling solutions makes it possible to create highly functional and beautifully engineered three-dimensional designs. The 20 mm joints are left open for an optimum thermal exchange with the concrete slab above.



Thermal activation

CCA reaches maximum efficiency if there is no barrier between the concrete structure and the underlying spaces. Independent climate chamber tests have shown that the aluminium used in Luxalon® CCA Acoustic+ 30BD and 30BXD panels and carriers is highly suited for cooling and heating as it functions as a thermal conductor. In combination with the relative openness of this ceiling system (50% openness with complete ceiling coverage), very positive results can be obtained.

Thermal capacity

Complete ceiling coverage results in a thermal capacity reduction of only 23% when compared to a bare CCA ceiling. During winter the reduction in the thermal capacity compared to a bare CCA ceiling is 6%, based on complete ceiling coverage.




Above : Waterschap Brabantse Delta, Breda, The Netherlands
 Product : CCA 30BD Linear Ceiling system
 Architect: Claus en Kaan Architecten Rotterdam

Key features

CCA 30BD-30BXD LINEAR OPEN CEILING

- Panel width: 30 mm, joint width 20 mm (standard) or 30 mm (CCA)
- Panel length: 800 mm up to 6000 mm
- Panel depths: 39 mm (BD) and 64 mm (30BXD)
- Carrier modules: 50 mm (standard) and 60 mm for enhanced heat exchange in CCA application
- On site waste reduction with factory fabricated dimensional material
- Easy plenum access
 Compatible with industry standard lighting, HVAC, speaker, fire safety, and security services




80B / 84B

A ceiling with character

The 80B/84B Linear Open Metal Ceiling system consists of box shaped panels which can be easily clipped onto a carrier. Known for its straight lines, versatility, and ease of installation, the 80B/84B linear open ceiling system creates a linear appearance providing a directional effect to a rooms interior. Panels are demountable for ease of access to the plenum.

System composition



HunterDouglas® 80B/84B Linear Ceiling system



Left : EKZ Mall, Liepziger Platz, Berlin, Germany
Product : 30BD and 80B Linear Metal Ceiling system
Architect: ARGE LP12

Dimensions & Colours

The 80B panels are 80 mm wide, 15 mm in height and have a 20 mm open joint between the panels. The 84B panels are 84 mm wide, 12.5 mm in height and have a 16 mm open joint. The 80B/84B panels can easily clipped on the 100 mm module carrier.

This metal ceiling is available in a variety of colours and finishes with perforation patterns for enhanced acoustic performance. See our colour card and availability chart on the website for standard available colours.



80B/84B Linear panel



Application

The 80B/84B linear open metal ceiling system is suitable for all building sectors including Corporate, Transport (airports, metro, bus and train stations), Retail, Leisure, Public space, Hospitality, Healthcare, Education and Residential.

Key features

80B/84B LINEAR CLOSED CEILING PANELS

- Panel width 80 mm, joint 20 mm (80B)
Panel width 84 mm, joint 16 mm (84B)
- Panel length: 800 mm up to 6000 mm
- Panel depth 15 mm (80B), 12.5 mm (84B)
- Optimum acoustic control using perforated panels with a non-woven textile
- Interior and exterior applications
- On site waste reduction with factory fabricated dimensional material
- Easy plenum access
- Compatible with industry standard lighting, HVAC, speaker, fire safety, and security services.

Left : Vitesse Trainingscomplex Papendal,
Arnhem, The Netherlands
Product : 80B Linear Metal Ceiling system




84R

Compose aesthetics with rounded linear fluid lines

Known for its fluid lines, versatility, and easy installation, The 84R Linear Open Ceiling system creates a rounded linear aesthetic. Slender rounded panels with 16 mm wide open joints enhance the linear appearance of the ceiling, providing a directional effect to a room. For a smoother appearance the joints can be closed with a join profile that is flush with the face of the panel.



System composition



HunterDouglas® 84R Linear Ceiling system

Left : Swimming pool
Product : 84R Linear Metal Ceiling

Dimensions & Colours

The 84R linear open ceiling system consists of round shaped panels which can be easily clipped onto a carrier. The 84 mm wide panels have a 16 mm open joint between the panels. The system module is 100 mm. Panels are demountable for easy access to the plenum.

A wide range of finishes are available including wood décor or on request in any desired RAL colour. See our colour card and availability chart on the website for standard available colours.

Application


The 84R open panel interior metal ceiling is suitable for all building sectors including Corporate, Transport (airports, metro, bus and train stations), Retail, Leisure, Public space, Hospitality, Healthcare, Education and Residential environments.

Key features


84R LINEAR OPEN CEILING PANELS

- Panel width 84 mm, joint 16 mm
- Panel length: 800 mm up to 6000 mm
- Panel depth 15 mm
- Round edges design
- Curved panel application available
- Curved carrier application available
- On site waste reduction with factory fabricated dimensional material
- Interior and exterior applications
- Compatible with industry standard lighting, HVAC, speaker, fire safety, and security services.

84R Linear panel



Below : National Aerospace Laboratory,
Marknesse, The Netherlands
Product : 84R Linear Metal Ceiling
Architect: Inbo Architecten




Project : Swimming pool
Product : 84R Linear Metal Ceiling




Where robustness and elegance come together

The 70U Linear Open Ceiling system is designed for those applications that require a more robust and stronger panel. Aluminium panels in combination with aluminium carriers make the system suitable for swimming pools and exterior applications. Steel carriers and steel panels are purpose designed for sports hall applications.

System composition



Luxalon® 70U Linear Ceiling system



Left : Metrostations, Bonn, Germany
Product : 70U Linear Ceiling system (Curved Carrier)

Dimensions & Colours

The 70U Linear Open Ceiling system consists of robust 70 mm wide (25 mm high) box shaped panels from steel or aluminium which are easily clipped onto the 70U carrier and create 30 mm wide, open joints. A standard range of finishes is available, also in steel, or on request in any desired RAL or custom colour (depending on quantity).

Application

The Open 70U Ceiling System is suitable for a range of building sectors including Transport (airports, metro, bus and train stations), Leisure, and Education environments.



Above : Swimming Pool Steinerbos, Stein, The Netherlands
Product : 70U Linear Ceiling system
Architect: Op 't Root en Beerts Architecten

70U Linear panel



Key features

70U LINEAR OPEN CEILING PANELS

- Panel width: 70 mm, joint width 30 mm
- Panel length: 800 mm up to 6000 mm
- Panel depth 25 mm
- Square edge design
- Curved carrier application available
- Tested on ball impact resistance
- On site waste reduction with factory fabricated dimensional material
- Easy plenum access
- Compatible with industry standard lighting, HVAC, speaker, fire safety, and security services.



Project : O.L.V. van Lourdescollege, The Netherlands
Product : 70U Linear Ceiling system (Curved Carrier)
Architect: RenE van Steenberghe




300C / 300L


Bring distinctive prominence to the ceiling

Our 300 mm wide ceiling panels establishes distinction in your project. The robust look of the 300C/300L Wide Panel Ceiling fits perfectly in large open spaces with a high level of noise. With two joint options and a variety of perforations for acoustic performance, our wide panels trim costs without trimming style.

System composition



HunterDouglas® 300C/300L Wide Panel Ceiling system



Project : Indianapolis Airport, Indianapolis IN, United States
Product : 300C Wide Panel Ceiling system
Architect: AeroDesign Group and HOK

Left : Ahoy, Rotterdam, The Netherlands
Product : 300C Wide Panel Ceiling system
Architect: AeroDesign Group and HOK

Dimensions & Colours

The 300C/300L Ceiling panels (height 29 mm) with a width of 300 wide mm have a lengths up to 6 m, requiring fewer panels and joints to reduce installation cost. One of the 4 standard support systems can be chosen to fit project requirements.

The wide choice of colours available make it possible to create virtually any ceiling design you can imagine. See our colour card and availability chart on the website for standard available colours.

Application


With excellent sound control properties, 300C/300L panels turn loud environments into spaces with a comfortable acoustic ambiance. 300C/ 300L Wide Ceiling Panels are suitable for all building sectors. These include corporate, transport (airports, metro, bus & train stations), retail, leisure, public space, hospitality, healthcare, education & residential environments.



300C panels (bevelled edge)



300L panels (straight edge)



Above : Radboud Hospital, Nijmegen, The Netherlands
Product : 300C Wide Panel Ceiling system
Architect: EGM Architecten




Above : Sporting Lissabon stadium, Lissabon, Portugal
Product : 300L Wide Panel Ceiling system
Architect: Tomas Taveira

Key features

WIDE PANEL CEILING

- Panel width: 300 mm
- Panel length: 1000 - 6000 mm
- Bevel-edge design and square edge design
- On site waste reduction with factory fabricated dimensional material
- Easy plenum access
- Interior and exterior applications
- Compatible with industry standard lighting, HVAC, speaker, fire safety, and security services.




84R Curved

Project : Food Market, Romania
Product : 84R Curved Metal Ceiling system
Architect: nn


'Lets twist and curve...' your ceiling

Luxalon® Curved Ceilings from Hunter Douglas add a twist to the traditional. Imagine concave, convex, and undulating forms that tempt a look upwards. Create soft curves, up to 90 degrees, and sculpted shapes with Luxalon® Curved Ceilings. The Luxalon® Curved Carrier system helps to transform standard flat panels into dynamic ceiling designs (see page 22).



Project : BME Q building, Budapest, Hungary
Product : 84R Curved
Architect: A&D Studio, Mr Antal Lázár

System composition



HunterDouglas® 84R Curved Panel Ceiling system (Convex)

300C Curved

Project : Brussels Airport Connector, Zaventem, Belgium
Product : 300C Curved
Architect: Joint Venture CTHM

Design elements

Luxalon® Curved Ceilings are the perfect way to create arches and multilevel designs. The curve doesn't need to stop at the ceiling. Luxalon® Curved ceilings can partially - or completely - clad surrounding walls.


With excellent acoustic properties and a variety of colours, finishes and curved options, these panels make it possible to create virtually any ceiling design you can imagine.

Key features


84R AND 300C CURVED CEILING

- Panel width: 84 mm (84R), 300 mm (300C)
- Joint width 16 mm (84R) and 0 mm (300C)
- Panel length: 1000 - 6000 mm
- Minimum radius for all shapes 1000 mm
- Panels in concave, convex or S-shape
- Curved carrier with straight panels (see page 22)
- On site waste reduction with factory fabricated dimensional material
- Interior and exterior applications
- Compatible with industry standard lighting, HVAC, speaker, fire safety, and security services

System composition



HunterDouglas® 300C Curved Panel Ceiling system (Concave)



Project : Piscine de Marcq, Ville de Marcq, France
Product : 300C Curved (Concave & Convex)
Architect: Service d'architecture de la ville de Marcq en Baroeul




Curved Carrier

Above : Fitness center World Class, Moscow, Russia
Product : 80B (Multipanel) Ceiling system (Curved Carrier)
Architect : PRIDEX

Consider a different and dramatic design

With Hunter Douglas Curved Carrier you can create curved shaped ceilings with straight panels. This design is possible when you use the Multi Panel system and the panel systems 84B, 84R, 70U and 300C.

Below : Underground Station, Rotterdam, The Netherlands
Product : 300C Wide Panel Ceiling (Curved Carrier)



Physical data

- Substrate: Steel or Aluminium
- Weight: Varies 1.7 - 5.3 kg/m²
- Light reflectance (LR) Coefficient:
 - Varies with finish
 - RAL9010: LR = 0.81
- Acoustic ratings: α_w 0.35 - 0.95 (H)

BIM

- REVIT files available, see website for details.

Fire classification

- Metal ceilings from Hunter Douglas are fully tested for reaction to fire according to EN 13501-1. More information is available on request.

Leed v4 credits

- MR : Building Product Disclosure
- EQ : Low-Emitting Materials
- EQ : Indoor Air Quality Assessment
- EQ : Acoustic Performance

Certifications

- TAIM QS
- French VOC Regulation: Class A
- C2C bronze

For more information visit our website:

www.hunterdouglas.co.uk

HunterDouglas 
Architectural

In the last 60 years, we have been fortunate enough to help turn countless innovative ideas into products for innovative buildings. With major operation centres in Europe, North America, Latin America, Asia and Australia we contribute to thousands of high-profile projects including shopping centres, airports, government offices, hospitals, universities and offices.



▲ CEILINGS



▲ WALLS



▲ SUN LOUVRES



▲ FAÇADES

Architectural services

We support our business partners with a wide range of technical consulting and support services for architects, developers, and installers. We assist architects and developers with recommendations regarding materials, shapes and dimensions, colours and finishes.

We also help creating design proposals, visualisations, and installation drawings. Our services to installers range from providing detailed installation drawings and instructions to training installers and advising on the building site.



Hunter Douglas adopts the cradle to cradle (C2C) product philosophy to the design of products that fit the circular paradigm. They are designed for longevity, using materially healthy technical nutrients that can be reused at end of life as a high-quality source for something new.

Cradle to Cradle Certified™ is a certification mark licensed by the Cradle to Cradle Products Innovation Institute.



Hunter Douglas products and solutions are designed to improve indoor environmental quality and conserve energy, supporting built environments that are comfortable, healthy, productive, and sustainable.



All steel products are 100% recyclable at the end of their lifecycle.



Printed on EU Ecolabel certified paper



All aluminium products are 100% recyclable at the end of their lifecycle.

More information

Contact our **Project Support** for further help and advice on the design possibilities our applications can create.

Call us:
+44 (0)1604 648 229

Send us an e-mail:
info@hunterdouglas.co.uk

Visit our website:
www.hunterdouglas.co.uk

ASIA | AUSTRALIA | LATIN AMERICA | NORTH AMERICA

Austria
Belgium
Bulgaria
Croatia / Slovenia
Czech Republic
Denmark
France

Germany
Greece
Hungary
Israel
Italy
The Netherlands
Norway

Poland
Portugal
Romania
Russia
Serbia
Slovakia
Spain

Sweden
Switzerland
Turkey
United Kingdom
South Africa
Middle East

CEILINGS



WALLS



SUN LOUVRE



FAÇADES



HUNTER DOUGLAS ARCHITECTURAL UNITED KINGDOM

Suite 2, Newton House, Northampton Science Park
Kings Park Road, Moulton Park Industrial Estate
Northampton, NN3 6LG
Tel: +44 (0)1604 648 229
info@hunterdouglas.co.uk
www.hunterdouglas.co.uk